



INJECTOR CLEANER DIESEL BARD AHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 05-12-16

Revision date: 16-02-17

Supersedes: 05-12-16 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : INJECTOR CLEANER DIESEL BARD AHL
Product code : 1037B # 737103BR1
Type of product : Detergent

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Function or use category : Cleaning/washing agents and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Distributor

SADAPS BARD AHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI - BELGIQUE
T +32 (0).69.59.03.60 - F +32 (0).69.59.03.61
msds@bardahlfrance.com - www.bardahlfrance.com

Supplier

SADAPS BARD AHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI - BELGIQUE
T +32 (0).69.59.03.60 - F +32 (0).69.59.03.61
msds@bardahlfrance.com - www.bardahlfrance.com

1.4. Emergency telephone number

Emergency number : + 32 (0)70.245.245 / +33 (0)1.45.42.59.59

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335
Specific target organ toxicity — Repeated exposure, Category 2 H373
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02



GHS07



GHS08



GHS09

Signal word (CLP) :

Danger

Hazardous ingredients :

xylene (mixture); 4-methylpentan-2-ol; Hydrocarbons, C10, aromatics, <1% naphtalene;; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hazard statements (CLP) :

H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

	H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness H373 - May cause damage to organs (central nervous system, kidneys, liver) through prolonged or repeated exposure H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (CLP)	: P102 - Keep out of reach of children P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P233 - Keep container tightly closed P260 - Do not breathe vapours P271 - Use only outdoors or in a well-ventilated area P273 - Avoid release to the environment P280 - Wear protective gloves, eye protection/face protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor P331 - Do NOT induce vomiting P302+P352 - IF ON SKIN: Wash with plenty of water P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P312 - Call a POISON CENTER, a doctor if you feel unwell P337+P313 - If eye irritation persists: Get medical advice/attention P391 - Collect spillage P403+P235 - Store in a well-ventilated place. Keep cool P501 - Dispose of contents/container to a hazardous or special waste collection point
EUH-statements	: EUH044 - Risk of explosion if heated under confinement
Extra phrases	: For professional users only

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC-No.) 918-481-9 (REACH-no) 01-2119457273-39	20-40	Asp. Tox. 1, H304
Hydrocarbons, C10, aromatics, <1% naphtalene;	(EC-No.) 918-811-1 (REACH-no) 01-2119463583-34	20-40	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
xylene (mixture)	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	10-20	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
4-methylpentan-2-ol	(CAS-No.) 108-11-2 (EC-No.) 203-551-7 (EC Index-No.) 603-008-00-8 (REACH-no) 01-2119473979-13	5-15	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335
2-ethylhexyl nitrate	(CAS-No.) 27247-96-7 (EC-No.) 248-363-6 (REACH-no) 01-2119539586-27	0-10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Aquatic Chronic 2, H411
Ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4 (REACH-no) 01-2119489370-35	<5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Toluene substance with national workplace exposure limit(s) (FR)	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3 (REACH-no) 01-2119471310-51	<0.5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

naphthalene substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (FR)	(CAS-No.) 91-20-3 (EC-No.) 202-049-5 (EC Index-No.) 601-052-00-2	<0.1	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
--	--	------	--

Specific concentration limits:

Name	Product identifier	Specific concentration limits
4-methylpentan-2-ol	(CAS-No.) 108-11-2 (EC-No.) 203-551-7 (EC Index-No.) 603-008-00-8 (REACH-no) 01-2119473979-13	(C >= 25) STOT SE 3, H335

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Remove contaminated clothes. Wash skin with plenty of water. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Water spray. Dry powder. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: Risk of explosion if heated under confinement.
Hazardous decomposition products in case of fire	: Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Prevent liquid from entering sewers, watercourses, underground or low areas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Evacuate area. Eliminate every possible source of ignition. Ensure adequate ventilation, especially in confined areas. Keep public away from danger area. Equip cleanup crew with proper protection.
------------------	--

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Recover the product with absorbent material.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it.

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Flammable liquid and vapour. Risk of explosion if heated under confinement.
Precautions for safe handling : Do not eat, drink or smoke when using this product.
Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry place. Store in a closed container. Store in a well-ventilated place. Keep out of frost. Keep away from heat.
Heat and ignition sources : Keep away from ignition sources. Do not smoke.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

xylene (mixture) (1330-20-7)		
France	VME (mg/m ³)	221 mg/m ³
France	VME (ppm)	50 ppm
France	VLE (mg/m ³)	442 mg/m ³
France	VLE (ppm)	110 ppm
Ethylbenzene (100-41-4)		
France	VME (mg/m ³)	551 mg/m ³
France	VME (ppm)	125 ppm
France	VLE (mg/m ³)	442 mg/m ³
France	VLE (ppm)	100 ppm
Toluene (108-88-3)		
France	VME (mg/m ³)	77 mg/m ³
France	VME (ppm)	20 ppm
France	VLE (mg/m ³)	384 mg/m ³
France	VLE (ppm)	100 ppm
Hydrocarbons, C10, aromatics, <1% naphthalene;		
France	VME (mg/m ³)	100
France	VME (ppm)	17 ppm
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics		
France	VME (mg/m ³)	1200 mg/m ³
France	VME (ppm)	184 ppm
Norway	Grænseverdier (AN) (mg/m ³)	275 mg/m ³
Norway	Grænseverdier (AN) (ppm)	50 ppm
2-ethylhexyl nitrate (27247-96-7)		
EU	IOELV TWA (ppm)	1 ppm
naphthalene (91-20-3)		
EU	IOELV TWA (mg/m ³)	50 mg/m ³
EU	IOELV TWA (ppm)	10 ppm
France	VME (mg/m ³)	50 mg/m ³
France	VME (ppm)	10 ppm

8.2. Exposure controls

Hand protection:

Protective gloves. EN 374

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)		3 (> 0.65)	EN 374

Eye protection:

Safety glasses. EN 166

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Type	Use	Characteristics	Standard
Safety glasses		With side shields	EN 166

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Good ventilation of the workplace required. Avoid inhalation of vapours



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: clear.
Colour	: Yellow.
Odour	: solvents.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 38 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0,835 - 0,845 (20°C)
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: < 20,5 mm ² /s (40°C)
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use. Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Risk of explosion if heated in a confined system.

10.4. Conditions to avoid

Heat. Open flame. Sparks. Water, humidity. Freezing.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

xylene (mixture) (1330-20-7)	
LD50 oral rat	2000 mg/kg
LD50 dermal	1100 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	1,5 mg/l/4h
LC50 inhalation rat (Vapours - mg/l/4h)	11 mg/l/4h

Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg
LD50 dermal rabbit	5000 mg/kg
LC50 inhalation rat (Vapours - mg/l/4h)	28,1 mg/l/4h

Hydrocarbons, C10, aromatics, <1% naphthalene;	
LD50 oral	> 10000 mg/kg
LD50 dermal	> 3160 mg/kg

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (mg/l)	4951 mg/m ³ 4 hours

Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified (64742-94-5)	
LD50 dermal rabbit	> 2 ml/kg
LC50 inhalation rat (mg/l)	> 590 mg/m ³

naphthalene (91-20-3)	
LD50 oral	490 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LD50 dermal	> 2500 mg/kg
LC50 inhalation rat (mg/l)	> 340 mg/m ³

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs (central nervous system, kidneys, liver) through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

INJECTOR CLEANER DIESEL BARDAHL	
Viscosity, kinematic	< 20,5 mm ² /s (40°C)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Acute aquatic toxicity : Not classified
Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

xylene (mixture) (1330-20-7)	
LC50 fish 1	2 - 11 mg/l
LC50 fish 2	13,5 mg/l
LC50 other aquatic organisms 1	21 mg/l
EC50 Daphnia 1	1 - 5 mg/l
EC50 72h algae (1)	3 - 5 mg/l

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethylbenzene (100-41-4)	
LC50 fish 1	12,1 mg/l
EC50 Daphnia 1	1,8 - 2,4 mg/l
EC50 72h algae (1)	438 mg/l

Toluene (108-88-3)	
LC50 fish 1	5,5 mg/l
EC50 Daphnia 1	3,78 mg/l
EC50 72h algae (1)	10 mg/l
LOEC (chronic)	2,77 mg/l 40 days onchorhynchus mykiss
NOEC chronic fish	1,39 mg/l 40 days onchorhynchus mykiss
NOEC chronic crustacea	10 mg/l

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LC50 fish 1	> 1000 mg/l
EC50 Daphnia 1	> 1000 mg/l
EC50 72h algae (1)	> 1000 mg/l

2-ethylhexyl nitrate (27247-96-7)	
LC50 fish 1	28,2 mg/l (Pimephales promelas, 4DY)
LC50 fish 2	17,1 mg/l (Ide mélanote (Leuciscus idus),4DY)
EC50 other aquatic organisms 1	> 12,6 mg/l (Cladocère, 2DY)

Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified (64742-94-5)	
LC50 fish 1	2 - 5 mg/l
EC50 Daphnia 1	3 - 10 mg/l
EC50 72h algae (1)	< 10 mg/l

naphthalene (91-20-3)	
LC50 fish 2	>= 2350 µg/l 48 hours
EC50 Daphnia 1	1,96 mg/l 48 hours

12.2. Persistence and degradability

xylene (mixture) (1330-20-7)	
Persistence and degradability	Readily biodegradable.

Ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable.

Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Biodegradation	80 % 28 days

12.3. Bioaccumulative potential

xylene (mixture) (1330-20-7)	
Log Pow	2,77 - 3,15
Bioaccumulative potential	not bioaccumulable.

Ethylbenzene (100-41-4)	
Log Pow	3,5

Toluene (108-88-3)	
Bioconcentration factor (BCF REACH)	90
Log Pow	2,65
Bioaccumulative potential	not bioaccumulable.

2-ethylhexyl nitrate (27247-96-7)	
Log Kow	5,24

12.4. Mobility in soil

xylene (mixture) (1330-20-7)	
Ecology - soil	insoluble in water. Floats on water.

Ethylbenzene (100-41-4)	
Ecology - soil	insoluble in water.

Toluene (108-88-3)	
Surface tension	0,0242 mN/m 20°C

INJECTOR CLEANER DIESEL BARD AHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-ethylhexyl nitrate (27247-96-7)

Mobility in soil (terre-3,75)

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available





SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not discharge into drains or the environment.
Product/Packaging disposal recommendations : Collect all waste in suitable and labelled containers and dispose according to local legislation.
Ecology - waste materials : Do not discharge the product into the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	RID
14.1. UN number			
1993	1993	1993	1993
14.2. UN proper shipping name			
FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.	Flammable liquid, n.o.s.	FLAMMABLE LIQUID, N.O.S.
Transport document description			
UN 1993 FLAMMABLE LIQUID, N.O.S. (CONTAINS ; xylene (mixture) ; Ethylbenzene), 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1993 Flammable liquid, n.o.s., 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)			
3	3	3	3
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available			

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 274, 601, 640E
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP29
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Orange plates :

30
1993

Tunnel restriction code (ADR) : D/E

- Transport by sea

Special provisions (IMDG) : 223, 274, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A

- Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

- Rail transport

Classification code (RID) : F1
Special provisions (RID) : 274, 601, 640E
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Detergent Regulation : Labelling of contents:

Component	%
aromatic hydrocarbons, aliphatic hydrocarbons	>=30%

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.1.2. National regulations

France

Occupational diseases : RG 4 BIS - Affections gastro-intestinales provoquées par le benzène, le toluène, les xylènes et tous les produits en renfermant
RG 84 - Affections engendrées par les solvants organiques liquides à usage professionnel

Germany

VwVwS Annex reference : Water hazard class (WGK) 3, severe hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : xylene (mixture), Toluene are listed

Denmark

Class for fire hazard : Class II-1

Store unit : 5 liter

Classification remarks : R10 <H226;H304;H315;H319;H335;H336;H373;H411>; Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H361d	Suspected of damaging the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
EUH044	Risk of explosion if heated under confinement

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product