



XTEC 0W30 LL

DESCRIPTION

High-performance, low-ash synthetic oil formulated to extend the life and maintain the efficiency of emission reduction systems for diesel, petrol and hybrid cars.

APPLICATION

BARDAHL XTEC 0w30 LL is based on Mid S.A.P.S./low HTHS technology and can be used for all engines requiring extended oil change intervals.

SPECIFICATIONS

This product offers the following performance level:

ACEA	C3
VW	504.00 / 507.00
BMW	LL 04
MERCEDES BENZ	229.31 / 229.51 / 229.52
PORSCHE	C 30

PROPERTIES

- ✓ Limits fuel overconsumption (special FE),
- ✓ Protects the lubricating film at high temperature,
- ✓ Makes cold start easier,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Excellent resistance to oxidation,
- ✓ Offers excellent stability at high temperature.



TECHNICAL DATA

Density at 15°C	Kg/l	0,844
Viscosity at -35°C	mPa.s	5750
Viscosity at 40°C	mm ² /s	64
Viscosity at 100°C	mm ² /s	12
Viscosity Index		178
Flash point COC, °C	°C	202
Pour point, °C	°C	-51
TBN Alcalinity	mgKOH/g	7,3
Sulphated Ash contents	%	0,78

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

34141	12 x 1 L
34143	3 x 5 L
34148	1 x 20L
34144	1 x 60L
34147	1 x 205 L