



# XTS 0W40

## DESCRIPTION

Fully synthetic engine oil formulated with last generation performance additives to reduce friction, eliminate sludge and optimize fuel consumption. Offers a good general protection of the engine.

## APPLICATION

**Bardahl XTS 0w40** provides an excellent resistance against shearing. It is suitable for powerful engines, turbo-charged or not, with or without direct injection. Compatible with any type of fuel.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	A3/B4
API	SN/CF
MERCEDES BENZ	229.3 / 226.5
VW	502.00/505.00
BMW	Longlife-01
RENAULT	RN0700/RN0710
PORSCHE	A40

## PROPERTIES

- ✓ Offers a stable viscosity and a high Viscosity Index,
- ✓ Preserves the protective lubricating film at high temperature,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold start easier,
- ✓ Provides an excellent resistance against « shearing ».



## TECHNICAL DATA

Density at 15°C	Kg/l	0,846
Viscosity at -35°C	mPa.s	6000
Viscosity at 40°C	mm <sup>2</sup> /s	83,7
Viscosity at 100°C	mm <sup>2</sup> /s	14
Viscosity Index		173
Flash point COC, °C	°C	232
Pour point, °C	°C	-45
TBN Alkalinity	mgKOH/g	10,5
Sulphated Ash contents	%	1,33

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

36141	12 x 1 L
36142	4 x 4 L
36143	3 X 5 L
36144	60 L
36147	205 L