

SAE90 MARINE Lower unit gear oil

DESCRIPTION

Fully synthetic extreme pressure oil formulated for the lubrication of heavy duty gears.

APPLICATION

The **SAE90 MARINE Lower unit gear oil** is particularly suitable for outboard and Z Drive motor lower unit gears, for transmissions, angle gears, reducers of pleasure boats.

SPECIFICATIONS

This product meets the following performance levels:

API	GL5
-----	-----

The **SAE90 MARINE Lower unit gear oil** is compatible with other mineral or synthetic lower unit gear oils except PAG.

PROPERTIES

- ✓ Very good Extreme Pressure (EP) properties,
- ✓ Excellent Viscosity Index (VI),
- ✓ High resistance against corrosion, in marine environment,
- ✓ High resistance against oxidation,
- ✓ Anti-wear, anti-foam.

DONNÉES TECHNIQUES

Density at 20°C	Kg/l	0,87
Viscosity 40°C	mm ² /s	75
Viscosity 100°C	mm ² /s	14,6
Viscosity Index		205
Flash point COC, °C	°C	214
Pour point, °C	°C	-27

RECOMMANDATIONS

Handling: all safety information on the handling and use of this product is provided in the Material Safety Data Sheet. Always check the manufacturer car manual before use.

Storage: it is recommended to use the product within 60 months. It must be stored in the original sealed packaging, protected from light, moisture and excessive temperatures.

RÉFÉRENCES ET DISPONIBILITÉS

2L x12	36932
60L	36934
205L	36937